



SPECIFICATIONS

TRAILER*

• SL 200

• SL 250

• SL 320

Length	42'4"	46'2"	52'6"
Width	8'2"	8'2"	8'2"
Height	13'2"	13'2"	13'5"
Cargo Space	27'6" x 5'10" x 7'4"	30' x 5'10" x 7'4"	38' x 4'6" x 7'4"
Storage Compartment	10" x 13" x 3'7"	10" x 13" x 3'7"	10" x 13" x 3'7"
Cargo Capacity with Gooseneck	13 000 lbs	13 000 lbs	5 000 lbs ††
Vehicle Weight	24 400 lbs	25 600 lbs	44 000 lbs

STAGE FLOOR

Length x Depth	30' x 24'	32' x 24'	40' x 32' or 40'
Length x Depth with extension platforms	Up to 46' x 36'	Up to 48' x 36'	Up to 60' x 48'
Height from Ground	3'6" to 5'3"	3'6" to 5'3"	3'6" to 6'
Capacity	100 lbs/sq ft	100 lbs/sq ft	100 lbs/sq ft
Type of Surface		Plywood on steel	

ROOF

Length x Depth	32' x 27'	34' x 27'	42' x 34' or 40'6"
Clearance (inclined roof)	15' to 18'6"	15' to 18'6"	17' to 21' or 22' to 26'
Maximum Height from Ground	23'6"	23'6"	27' or 32'
Type of Surface		Fiberglass bonded on steel	
Load Bearing Capacity	12 000 lbs	12 000 lbs	16 000 lbs
8 Rated Rigging Points	1 000 lbs each	1 000 lbs each	1 000 lbs each
2 Front Overhang Extensions	500 lbs at 5' each	500 lbs at 5' each	500 lbs
2 Side Overhang Rigging Bars (sound wings)	1 000 lbs at 3' each	1 000 lbs at 3' each	500 lbs at 3' each
2 Side Overhang Extensions (Option)	2 000 lbs at 6'	2 000 lbs at 6'	2 x 2 000 lbs at 6' apart
2 Rear Overhang Extensions	—	—	500 lbs

PRACTICAL ASPECTS

Installation time once levelling is complete †	1 hour / 1 technician	2-3 hours / 2 technicians
Personnel required	1 stagehand	2 stagehands
Site preparation		None
Heavy machinery required		None
Mode of transportation	1 standard tractor trailer	
Wind resistance	50 to 70 mph	
Tailored windwalls	Weatherproof, fire-retardant vinyl	
Sponsor visibility	Rolling billboard, giant or smaller banners adapt to structure	
Side overhang extensions for banners	Slide out of rigging bars to 12'	
Banner hardware	Compact add-on attachments	
Platform Supports	Rapid installation of covered sound wings	

† Values indicated are nominal.
 * Specifications can be modified to suit a particular country's highway regulations.

† Less time required without windwalls and / or sound wings under ideal conditions.
 †† Increased capacity with third axle.
 Due to STAGELINE'S product improvement policy, technical specifications may change without notice.

ALL STAGE & SOUND INC.
"Keeping You Above The Crowd"
 Gaithersburg, MD

 (888) ALL-STAGE

ALL STAGE & SOUND INC.
"Keeping You Above The Crowd"
 Gaithersburg, MD

 (888) ALL-STAGE

ALL STAGE & SOUND INC.
"Keeping You Above The Crowd"
 Gaithersburg, MD

 (888) ALL-STAGE



SPECIFICATIONS

TRAILER*

•SL 200

•SL 250

•SL 320

Length	12.9 m	14.1 m	16 m
Width	2.5 m	2.5 m	2.5 m
Height	4 m	4 m	4.1 m
Cargo Space	8.4 x 1.8 x 2.2 m	9.1 x 1.8 x 2.2 m	11.6 x 1.4 x 2.2 m
Storage Compartment	0.25 x 0.25 x 1.1 m	0.3 x 0.3 x 1.1 m	0.3 x 0.3 x 1.1 m
Cargo Capacity with Gooseneck	5 900 kg	5 900 kg	2 260 kg ††
Vehicle Weight	11 500 kg	12 000 kg	19 000 kg

STAGE FLOOR

Length x Depth	9.1 m x 7.3 m	9.8 m x 7.3 m	12.2 m x 9.8 m or 12.2 m
Length x Depth with extension platforms	Up to 14 x 11 m	Up to 14.6 x 11 m	Up to 18.3 x 14.6 m
Height from Ground	1.1 m to 1.6 m	1.1 m to 1.6 m	1.1 m to 1.8 m
Capacity	500 kg/m ²	500 kg/m ²	500 kg/m ²
Type of Surface		Plywood on steel	

ROOF

Length x Depth	9.8 m x 8.2 m	10.4 m x 8.2 m	12.8 m x 10.4 m or 12.3 m
Clearance (Inclined roof)	4.6 m to 5.6 m	4.6 m to 5.6 m	5.2 to 6.4 m or 6.7 to 7.9 m
Maximum Height from Ground	7.2 m	7.2 m	8.2 m or 9.8 m
Type of Surface		Fiberglass bonded on steel	
Load Bearing Capacity	5450 kg	5450 kg	7260 kg
8 Rated Rigging Points	454 kg ea.	454 kg ea.	454 kg ea.
2 Front Overhang Extensions	227 kg at 1.5 m ea.	227 kg at 1.5 m ea.	227 kg
2 Side Overhang Rigging Bars (sound wings)	454 kg at 0.9 m ea.	454 kg at 0.9 m ea.	227 kg at 0.9 m ea.
2 Side Overhang Extensions (Option)	908 kg at 1.8 m ea.	908 kg at 1.8 m ea.	2 x 908 kg at 1.8 m apart
2 Rear Overhang Extensions			227 kg

PRACTICAL ASPECTS

Installation time once levelling is complete †	1 hour / 1 technician	2-3 hours / 2 technicians
Personnel Required	1 stagehand	2 stagehands
Site Preparation	None	
Heavy Machinery Required	None	
Mode of Transportation	1 standard tractor trailer	
Wind Resistance	80 to 115 km/h	
Tailored Windwalls	Weatherproof, fire-retardant vinyl	
Sponsor Visibility	Rolling billboard, giant or smaller banners adapt to structure	
Banner Overhang Extensions	Slide out of rigging bars to 3.7 m	
Banner Hardware	Compact add-on attachments	
Platform Supports	Rapid installation of covered sound wings	

ALL STAGE & SOUND INC.

"Keeping You Above The Crowd"
Gaithersburg, MD

(888) ALL-STAGE



without notice.

info@stageline.com - www.stageline.com

Date:15-02-01; Ref. number: S09-V-020; REVISION:3